

**Spindle-Saw B3 Winner**

M002026

- ✓ Year of construction 2021
- ✓ Available immediately

**Technical Data**

- 4.0 HP 3x400V CE
- Spindle rotating left and right
- Saw blade manually pivotable 90°-45°
- Max. cutting height : 103 mm
- Professional circular saw stop in cast iron, cutting width : 800 mm
- Spindle manually tiltable 90°-45°
- 4 RPM cutter : 3,000/6,000/8,000/10,000 rpm
- Milling table opening : 180 mm
- Interchangeable router spindle Ø 30 mm, 100 mm working height
- Cutter stop 220 for tool Ø max. 220 mm
- Panel saw carriage : 2000 mm
- Outrigger table 1100 mm with degree grid index and crosscut fence 1300 mm
- Saw extraction connection : 120/50 mm (extraction capacity 814 m³/h)
- Cutter : 120 mm (extraction capacity 362 m³/h)
- Aluminium parallel guide
- Multi-adjustment system with stop shoes 450 mm
- Prepared for adjustable groove cutter up to 19.5 mm width
- Mechanically driven scoring unit Ø 80 mm
- Fine adjustment for circular saw stop profi
- System handwheel for recording digital clock

**Machine is still in original transport packaging, photo not complying**