

Spindle-Saw KF 700 S Professional

M002029

- ✓ Year of construction 2021
- ✓ Available immediately



Technical Data

3 x 400V - motor 7.5 HP (5.5 kW) incl. star-delta starter
 Potential current-free contact - ONLY for RL dust extraction units equipped with automatic starting device
 Direction of rotation switch
 Circular saw with manual tilt 90°-45°
 Max. cutting height 104 mm
 EURO II Standard protective cover
 Spindle moulder with 90°-45° manual tilt
 4 speeds: 3500/6500/8000/10,000 rpm
 Router table opening: 230 mm
 Interchangeable spindle moulder blade Ø 30 mm,
 useful height 115 mm
 Router guard 230 ,
 Max. tool Ø 230 mm
 EURO spindle moulder guard
 MULTI-adjustment system
 Electric height + angle adjustment saw incl. LED display ('Power-Drive' K2)
 Prepared for adjustable groove cutters up to 19.5 mm width
 Fine-adjustable parallel stop
 Motorised front zip - diameter 100 mm with saw blade diameter 300 mm
 Cutting width 1250 mm
 Suction hose guide for cutting width 1250 mm
 Electric height and angle adjustment cutter with LED display 'Power-Drive F2'
 Roller carriage X-roll sawing length 3200mm
 Switch-on option on roller carriage for main motor (and front zip)
 Support table 1500mm
 Angle stop 3200mm with 2 clickers

The photo is not binding, the machine is still in its transport packaging.

